



Putzmeister

Your benefits

- Kubota diesel engine (Emissions standard Stage 3B) water-cooled, eco-friendly with integrated particle filter for optimised performance
- Innovative exhaust air routing and additional exhaust duct for improved cooling output and better operability
- With automatic brake adjustment for added driving safety and comfort
- Protected innovative display incl. "Troubleshooting" and "Service information"
- Clearly arranged keypad with colour LED display
- Optimised maintenance and service features
- Robust design ensures value retention and high resale values
- Made in Germany

Mixokret M 760 3B Screed Pump = Eco-friendly + max. Power



The M 760 3B conveys screed up to 200 metres* horizontally and 150 metres* vertically. The keypad with innovative, colour LED display in the control cabinet makes operation incredibly simple and efficient. The menus for troubleshooting and servicing improve availability.

The Kubota diesel engine (Emissions level Stage 3B) offers even more power. The integrated diesel particle filter cleans the exhaust gases and protects our environment.

For further information related to technical details or application, please contact your local Putzmeister dealer.

- **Cement screed**
- **Calcium sulphate screed** (anhydrite)
- **Magnesia screed**



Semi-dry
floor screed



Most powerful Mixokret, with a water-cooled, 4-cylinder Kubota diesel engine and with integrated particle filter.



The new 8 button keypad with colour LED display is very clearly arranged and easy to use.



The innovative exhaust air routing and an additional exhaust duct improve the working area.

Technical data

	M 760 DH 3B	M 760 DHB 3B	M 760 DHBS 3B
Mixer drum	260 l, 200 l useful cap.	260 l, 200 l useful cap.	260 l, 200 l useful cap.
Delivery rate*	4 m ³ /h	4.8 m ³ /h	5 m ³ /h
Delivery pressure	8 bar	8 bar	8 bar
Delivery range**	200 m horizontally / 150 m vertically (50 storeys)		
Compressor	5.0 m ³ /min; cut-off pressure 8 bar		
Engine	Kubota 4-cylinder diesel, water-cooled 48.5 kW at 2700 rpm (emission stage 3B)		
Weight (fully fuelled)	1,720 kg	1,826 kg	1,900 kg
Tank capacity	approx. 70 l	approx. 70 l	approx. 70 l
Length	4,780 mm	5,075 mm	5,075 mm
Width	1,480 mm	1,480 mm	1,480 mm
Height	1,520 mm	2,431 mm	2,431 mm
Filling height	820 mm	400 mm	400 mm
Maximum grain size	16 mm	16 mm	16 mm
Chassis	braked, with automatic brake adjustment approved for speeds up to 80 km/h		
Special feature	Basis version	with hydraulic feeder	with hydraulic feeder and scraper

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

Automatic brake adjustment	■
Car coupling	■
Central lubrication system	■
Discharge stand	■
Grease pump for lubrication system	■
Instruction manual and spare parts list	■
Lever Press with hose	■
Lifting eye	■
Reservoir gauge in control panel	■
Working lights	■
Auto-Power-Off	□
Conversion to 100 km/h	□
High-pressure cleaner	□
Light holder 24 V	□
Location system	□
Mixing time adjustment	□
Performance management	□
Special canopy paint in RAL colours/Custom labelling	□
Support feet	□
Truck coupling	□
Wear plates at the dome	□
Wear plates front end (impact protection bars)	□
Wear plates, highly wear-resistant (lateral)	□
Wear plates, plastic	□

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@pmw.de · www.pmmortar.de

