



**Putzmeister**

## Your benefits

- Large mixer/hopper for more efficient working
- Water metering pipe in the mixer grill prevents blockages
- Lifting mixer with low filling height for convenient filling
- Conforms with CE standards, simple and clear operation
- Extremely effective mixing apparatus
- Infinitely variable pumping rate
- Fully hydraulic pump and mixing drive
- 4-cylinder engine generates 22.7 kW of power, with large 26 l diesel tank
- Optimal soundproofing thanks to double-walled canopy
- Support wheel for excellent manoeuvrability with low drawbar load
- Optional patented dust extraction system in the mixer grill
- Made in Germany

## SP 11 TMR – Outstanding performance for a wide variety of applications



The lightweight and compact SP 11 TMR worm pump from Putzmeister was designed for high delivery rates. The pump can effortlessly convey material over distances of 70 m and to heights of 50 m.

The power of the SP 11 TMR from Putzmeister is ideal to mix, pump and even spray site-mixes or pre-mixed interior and external plasters supplied in bags, monocoat, fire-proofing mortar, base coat plaster, lightweight masonry mortar, ornamental plaster, self-leveling floor screed as well as filling and grouting work.

Your expert Putzmeister dealer will be glad to provide you with further information according to your individual requirements.

- **Exterior plaster** (lime, lime cement and insulating plaster)
- **Interior plaster** (lime plaster)





The extremely powerful 4-cylinder engine is exceptionally quiet due to the speed of only 2,600 rpm and extremely effective sound insulation.



The 2L6 pump (see image) and more powerful 2L75 pump are available, depending on the required delivery rate and material consistency.



The intelligently positioned water metering pipe prevents blockages and the optional patented dust extraction system ensures a convenient filling process.

## Technical data

## SP 11 TMR

<b>Mixer drum</b>	180 l
<b>Feed hopper</b>	220 l
<b>Delivery rate*</b>	5-75 l/min, optional: up to 15 m <sup>3</sup> /h
<b>Delivery pressure</b>	35 bar, optional: 20 bar
<b>Delivery range**</b>	70 m horizontal and 50 m vertical for exterior/interior plaster
<b>Compressor</b>	2-cylinder, 400 l/min, 7 bar
<b>Pump</b>	Worm pump 2L6, optional: 2L75
<b>Engine</b>	4-cylinder Kubota diesel, 22.7 kW at 2,600 rpm
<b>Weight (fully fuelled)</b>	900 kg
<b>Length x width x height</b>	3,820 x 1,420 x 1,160 mm
<b>Filling height</b>	880 mm
<b>Maximum particle size</b>	6 mm (2L6), 8 mm (2L75)
<b>Chassis</b>	braked, approved for road use
<b>Maximum particle size</b>	6 mm (2L6), 8 mm (2L75)

\* The delivery rate is theoretical and depends on the pump pressure.

\*\* The data is based on experience and is dependent on the materials used.

## Equipment

Car cable adapter	■
Car coupling	■
Cleaning tool	■
Grease cartridge	■
High-pressure cleaner	■
Instruction manual and spare parts list	■
Lever press with hose	■
Mechanical water metering	■
Seal ring for mortar coupling	■
Standard colour paintwork	■
Standard tool	■
Support wheel	■
Cable remote control 20 m	□
Dust extraction	□
Radio remote control 20 m	□
Special canopy paint in RAL colours	□
Truck coupling	□
Vibrating screen	□
Working lights	□

□ Optional ■ Standard

## Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany  
P.O.Box 2152 · 72629 Aichtal / Germany  
Tel. +49 7127 599-0 · Fax +49 7127 599-743  
mm@pmw.de · www.pmmortar.de

